



Qty	Part Number	Size I.D. (in)	A ± 1/8 (in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	GFC0200	2	12	450	9	
	GFC0250	2-1/2	14	345	13	
	GFC0300	3	14	289	14	
	GFC0400	4	16	300	18	
	GFC0500	5	17	220	25	
	GFC0600	6	18	200	28	
	GFC0800	8	20	190	52	
	GFC1000	10	24	150	75	
	GFC1200	12	25	125	100	

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"
 MAX PERMANENT OFFSET FROM CENTERLINE 3/8"

*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<h2>MODEL GF</h2> <h3>STAINLESS STEEL PUMP CONNECTOR</h3>	
DRAWN BY: DKISH	DATE: 1/10/2014
APPROVED: JC	DATE: 1/10/2014
SCALE: NONE	DRAWING NUMBER: GFC