



Qty	Part Number	Size I.D. (in)	A ± 1/8 (in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	MLPC0200	2	12	455	12	
	MLPC0250	2-1/2	12	345	13	
	MLPC0300	3	14	289	15	
	MLPC0400	4	16	300	20	
	MLPC0500	5	18	220	30	
	MLPC0600	6	20	200	34	
	MLPC0800	8	22	190	68	
	MLPC1000	10	24	150	75	
	MLPC1200	12	26	125	112	
	MLPC1400	14	28	105	128	

MAX INTERMITTENT OFFSET FROM CENTERLINE 3/4"
 MAX PERMANENT OFFSET FROM CENTERLINE 1"

*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL MLP STAINLESS STEEL PUMP CONNECTOR	
DRAWN BY: DKISH	DATE: 1/10/2014
APPROVED: JC	DATE: 1/10/2014
SCALE: NONE	DRAWING NUMBER: MLP