



*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

Qty	Model #	A (in)	B (in)	F/F (in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	RMF0215	2	1-1/2	12-1/4	345	10	
	RMF2502	2-1/2	2	12-1/4	345	15	
	RMF0302	3	2	12-1/4	289	17	
	RMF0325		2-1/2				
	RMF0402	4	2	12-3/4	300	22	
	RMF0425		2-1/2				
	RMF0403		3				
	RMF0525	5	2-1/2	15-3/4	220	31	
	RMF0503		3				
	RMF0504		4				
	RMF0602	6	2	16-1/4	200	36	
	RMF0625		2-1/2				
	RMF0603		3				
	RMF0604		4				
	RMF0605		5				
	RMF0804	8	4	17-1/2	190	65	
	RMF0805		5				
	RMF0806		6				
	RMF1006	10	6	19-1/2	150	97	
	RMF1008		8				
	RMF1206	12	6	21-1/2	125	137	
	RMF1208		8				
	RMF1210		10				

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"
 MAX PERMANENT OFFSET FROM CENTERLINE 3/8"

LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<h2>MODEL RMF</h2> <h3>STAINLESS STEEL REDUCING CONNECTOR</h3>	
DRAWN BY: DKISH	DATE: 1/10/2014
APPROVED: JC	DATE: 1/10/2014
SCALE: NONE	DRAWING NUMBER: RMF