

Qty	Part Number	A (in)	B (in)	C (in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	RSSC2503	2 1/2	3	9	345	12	
	RSSC2504	2 1/2	4	9	345	14	
	RSSC0304	3	4	9	289	16	
	RSSC0305	3	5	9	289	22	
	RSSC0405	4	5	9	300	25	
	RSSC0406	4	6	9	300	30	
	RSSC0506	5	6	11	220	35	
	RSSC0508	5	8	11	220	58	
	RSSC0608	6	8	11	200	61	
	RSSC0610	6	10	11	200	80	
	RSSC0810	8	10	12	190	85	
	RSSC0812	8	12	12	190	105	
	RSSC1012	10	12	13	150	132	

*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"
MAX PERMANENT OFFSET FROM CENTERLINE 3/8"


LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<h2>MODEL RSS</h2> <h3>REDUCING STAINLESS STEEL CONNECTOR</h3>	
DRAWN BY: DKISH	DATE: 1/10/2014
APPROVED: JC	DATE: 1/10/2014
SCALE: NONE	DRAWING NUMBER: RSSC