



Qty	Part Number	Size I.D. (in)	A ± 1/8(in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	SLPC0250	2-1/2	10-1/4	345	13	
	SLPC0300	3	10-5/8	289	14	
	SLPC0400	4	11-3/4	300	19	
	SLPC0500	5	13-5/8	220	27	
	SLPC0600	6	14-1/8	200	30	
	SLPC0800	8	15-3/8	190	62	
	SLPC1000	10	17-3/4	150	68	
	SLPC1200	12	18-3/8	125	106	
	SLPC1400	14	20	105	118	

\*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

MAX INTERMITTENT OFFSET FROM CENTERLINE 3/8"  
 MAX PERMANENT OFFSET FROM CENTERLINE 3/4"

### LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<h2>MODEL SLP</h2> <h3>STAINLESS STEEL PUMP CONNECTOR</h3>	
DRAWN BY: DKISH	DATE: 1/10/2014
APPROVED: JC	DATE: 1/10/2014
SCALE: NONE	DRAWING NUMBER: SLP