



Note: Do not use wrenches on hose or braid collar.

Qty	Part Number	Size I.D. (in)	A ± 1/8 (in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	SSTT0038	3/8	6	1600	1	
	SSTT0050	1/2	6-1/2	1100	1.2	
	SSTT0075	3/4	7	792	1.5	
	SSTT0100	1	8	571	2	
	SSTT0125	1-1/4	8-1/2	531	2.5	
	SSTT0150	1-1/2	9	472	3	
	SSTT0200	2	10-1/2	500	4	

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"

\*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

### LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.



CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<b>MODEL SSTT</b> <b>THREADED METAL CONNECTOR</b>	
DRAWN BY: DKISH	DATE: 1/10/2014
APPROVED: JC	DATE: 1/10/2014
SCALE: NONE	DRAWING NUMBER: SSTT