



MATERIALS OF CONSTRUCTION*

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 90° ELBOW - CARBON STEEL - SCH 40/STD WT
 180° RETURN - CARBON STEEL - SCH 40/STD WT
 *OTHER MATERIALS AVAILABLE

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

NOTE: METRALOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MVMT	A	B	PSI*	WT (LBS)	SPRING FORCE**	PROJECT INFO
	2	MLG30200	+/- 1.5	18	17.375	500	15	78	
	2.5	MLG30250	+/- 1.5	21	21	387	23	83	
	3	MLG30300	+/- 1.5	24	23.375	288	39	90	
	4	MLG30400	+/- 1.5	30	28	232	54	120	
	5	MLG30500	+/- 1.5	36	32.25	191	89	186	
	6	MLG30600	+/- 1.5	42	36.75	165	135	202	
	8	MLG30800	+/- 1.5	56	44.5	212	264	260	
	10	MLG31000	+/- 1.5	68	53.25	175	430	283	
	12	MLG31200	+/- 1.5	80	61.75	160	592	390	

*Working pressure listed is the rating at 70° F. Contact factory for other pressure ratings at other temperatures and for steam applications.

**Spring force: The total force (Lbs) required to move the Metraloop its full rated movement for 150 PSI @ 70°F.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	1	SUPPORT BRACKET CHANGE DATE	2/5/2015
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
METRALOOP® GROOVED ENDS, +/- 1.5" MOVEMENT			
DRAWN BY: DKISH		DATE: 10/29/2014	
APPROVED: JC		DATE: 10/29/2014	
SCALE:	DRAWING NUMBER:		
NONE	MLG3-REV1		