



MATERIALS OF CONSTRUCTION*

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 90° ELBOW - CARBON STEEL - SCH 40/STD WT
 180° RETURN - CARBON STEEL - SCH 40/STD WT
 *OTHER MATERIALS AVAILABLE

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

NOTE: METRALOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MVMT	A	B	PSI*	WT (LBS)	SPRING FORCE**	PROJECT INFO
	2	MLG80200	+/- 4	20	24.5	500	18	78	
	2.5	MLG80250	+/- 4	21.5	28.25	387	29	83	
	3	MLG80300	+/- 4	24	30	288	43	90	
	4	MLG80400	+/- 4	30	35.375	232	60	120	
	5	MLG80500	+/- 4	36	40.25	191	99	186	
	6	MLG80600	+/- 4	42	45.375	165	150	202	
	8	MLG80800	+/- 4	56	53.5	212	286	260	
	10	MLG81000	+/- 4	68	63.25	175	461	283	
	12	MLG81200	+/- 4	80	72.75	160	622	390	

*Working pressure listed is the rating at 70° F. Contact factory for other pressure ratings at other temperatures and for steam applications.

**Spring force: The total force (Lbs) required to move the Metraloop its full rated movement for 150 PSI @ 70°F.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	1	SUPPORT BRACKET CHANGE	DATE	2/5/2015
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM		
METRALOOP® GROOVED ENDS, +/- 4" MOVEMENT				
DRAWN BY: DKISH		DATE: 10/29/2014		
APPROVED: JC		DATE: 10/29/2014		
SCALE:	DRAWING NUMBER:			
NONE	MLG8-REV1			