



This is a flexible member and adjacent pipe must be properly anchored and guided. Coupling to be slipped over pipe to a depth of 2". Torque nuts to 225 inch-pounds.

Qty.	Pipe Size (in)	Size I.D. (in)	F/F (in)	Pressure (PSI)	Vacuum (in Hg)	Comp. (in)	Elong. (in)	Angular (Degrees)	Weight (Lbs)
	2	2 3/8	7	75	20	1	1/2	10	1.6
	2 1/2	2 7/8	7	75	20	1	1/2	10	1.8
	3	3 1/2	7	75	20	1	1/2	10	2.0
	3 1/2	4	7	75	20	1	1/2	10	2.2
	4	4 1/2	7	75	20	1	1/2	10	2.4
	4 1/2	5	7	75	20	1	1/2	10	2.7
	5	5 5/8	7	75	20	1	1/2	10	2.9
	6	6 5/8	7	75	20	1	1/2	10	3.4
	8	8 5/8	7	75	20	1	1/2	10	4.3
	10	10 3/4	7	75	20	1	1/2	10	5.1
	12	12 3/4	7	75	20	1	1/2	10	6.7

MAXIMUM WORKING TEMPERATURE 225°F

NOTES

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<b>STYLE 201</b> FLEXIBLE COUPLING	
DRAWN BY: <b>DKISH</b>	DATE: <b>11/4/2014</b>
APPROVED:	DATE:
SCALE: <b>NONE</b>	DRAWING NUMBER: <b>201</b>