



LEAD FREE - NSF 372

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

OPERATING TEMPERATURE AND PRESSURE:

Water, Oil, Gas (Non-Shock) - 200 PSI at 150°F

ITEM	PART NAME	MATERIAL
1	BODY	304 STAINLESS STEEL
2	CAP	304 STAINLESS STEEL
3	BLOWOFF PLUG	304 STAINLESS STEEL
4	GASKET	TFE
5	SCREEN	STAINLESS STEEL
6	FEMALE SWEAT END	COPPER

QTY	PART NUMBER	SIZE I.D. (in)	A (in)	B (in)	WEIGHT (Lbs)	BLOWOFF SIZE NPT	PROJECT INFO
	SSFS0050	1/2	3-1/2	1-1/2	0.60	1/4	
	SSFS0075	3/4	5	1-7/8	0.80	3/8	
	SSFS0100	1	5-7/8	2-1/8	1.20	3/8	
	SSFS0125	1-1/4	6-3/4	2-1/2	1.90	3/8	
	SSFS0150	1-1/2	7-7/8	3	2.70	1/2	
	SSFS0200	2	9-1/8	3-3/8	4.30	1/2	

SERVICE	SIZES	SCREEN OPENINGS	SCREEN MATERIAL
LIQUID	1/2" - 2"	20 MESH EQUIVALENT, EXPANDED METAL DIAMOND PERFORATIONS	STAINLESS STEEL

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL SSFS Y-TYPE 150# STAINLESS STEEL STRAINER, FEMALE SWEAT END	
DRAWN BY: DTH	DATE: 4/16/2015
APPROVED: JC	DATE: 4/16/2015
SCALE: NONE	DRAWING NUMBER: SSFS