



MAX NON-SHOCK
WORKING PSI

TEMPERATURE	PSI
150°F	200
200°F	190

LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

Notes:

Valve is designed for liquid service only. Install 5 to 10 pipe diameters downstream from pump discharge or elbows to avoid flow turbulence.

Valve complies with MSS-SP-125-2010.



FOR ADDITIONAL FLOW STRAIGHTENING
SEE THE VANE FLEX AT
www.metroflex.com/vaneflex

ITEM	PART NAME	MATERIAL	ASTM NO.
1	BODY	CAST IRON	A126 CL. B
2	SEAT	STAINLESS	T304
3	PLUG	STAINLESS	T304
4	SPRING	STAINLESS	T304
5	BUSHING	STAINLESS	T304
6	SCREW	STAINLESS	T304
7	GROOVED END	DUCTILE IRON	A395
8	150# GASKET	GRAPHITE	N/A
9	THREADED ROD	CARBON STEEL	A307

Qty.	Part Number	Valve Size (in)	A (in)	B (in)	Cv*	Weight (Lbs)	Project Info
	CVGSS702	2	6	6	66	14	
	CVGSS7025	2-1/2	6-1/4	7	88	20	
	CVGSS703	3	6-7/16	7-1/2	130	26	
	CVGSS704	4	8-1/8	9	228	42	
	CVGSS705	5	11-1/4	10	350	60	
	CVGSS706	6	12-1/4	11	520	79	
	CVGSS708	8	13-3/4	13-1/2	900	152	
	CVGSS710	10	16	16	1450	225	

*Cv is the number of U.S. gallons/minute of 60°F water that will flow through a valve with 1 PSI of pressure drop across the valve.

REV.	1	WEIGHTS/DRAWING UPDATED	DATE 11/25/2013
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<h2>MODEL CVG700-SS</h2>			
GROOVED-END WAFER STYLE SILENT CHECK VALVE W/ SS TRIM			
DRAWN BY: DKISH		DATE: 8/27/2013	
APPROVED: JC		DATE: 8/27/2013	
SCALE: NONE	DRAWING NUMBER: CVG700-SS		

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____